

Dimensions

Condensing unit	Standard construction ①									Unit with Housing ②							
	Overall dimensions			Condenser dimensions		Fixing holes position		Drawing		Overall dimensions				Drawing		Housing	
	Length	Width	Height	Length	Height	Distance between holes	Distance from side A	Ref.	Page	Length	Width (base)	Width (max)	Height	Ref.	Page	Weight	Code
	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Nr.	Nr.	A mm	B mm	C mm	D mm	Nr.	Nr.	kg	
LB-Q528-0Y-2M	1.060	760	575	998	522	615	72,5	7	50	1.010	762	783	547	7	50	33	USH0U16
LBT-Q528-0Y-2T	1.420	760	689	1.358	522	615	72,5	8	50	1.370	762	783	660	8	50	44	USH0U15
LB-Q728-0Y-2T	1.420	760	689	1.358	635	615	72,5	7	50	1.370	762	783	660	7	50	44	USH0U15
LBT-Q728-0Y-2T	1.570	830	864	1.508	810	665	72,5	8	50	1.520	832	853	835	8	50	54	USH0U14
LB-Q533-0Y-2M	1.060	760	575	998	522	615	72,5	7	50	1.010	762	783	547	7	50	33	USH0U16
LBT-Q533-0Y-2T	1.420	760	689	1.358	522	615	72,5	8	50	1.370	762	783	660	8	50	44	USH0U15
LB-Q733-0Y-2T	1.420	760	689	1.358	635	615	72,5	7	50	1.370	762	783	660	7	50	44	USH0U15
LBT-Q733-0Y-2T	1.570	830	864	1.508	810	665	72,5	8	50	1.520	832	853	835	8	50	54	USH0U14
LB-Q536-0Y-2T	1.420	760	689	1.358	635	615	72,5	7	50	1.370	762	783	660	7	50	44	USH0U15
LBT-Q536-0Y-2T	1.570	830	864	1.508	810	665	72,5	8	50	1.520	832	853	835	8	50	54	USH0U14
LB-Q736-0Y-2T	1.420	760	689	1.358	635	615	72,5	7	50	1.370	762	783	660	7	50	44	USH0U15
LBT-Q736-0Y-2T	1.570	830	864	1.508	810	665	72,5	8	50	1.520	832	853	835	8	50	54	USH0U14
LB-S842-3Y-2T	1.420	760	689	1.358	635	615	72,5	9	51	1.370	812	833	660	9	51	45	USH0U13
LBT-S842-3Y-2T	1.570	830	864	1.508	810	685	72,5	10	51	1.520	832	853	835	10	51	54	USH0U14
LB-S1242-3Y-2T	1.570	830	864	1.508	810	685	72,5	9	51	1.520	832	853	835	9	51	54	USH0U14
LBT-S1242-3Y-2T	1.570	830	864	1.508	810	685	72,5	10	51	1.520	832	853	835	10	51	54	USH0U14
LB-S1052-3Y-2T	1.420	760	689	1.358	635	615	72,5	9	51	1.370	812	833	660	9	51	45	USH0U13
LBT-S1052-3Y-2T	1.570	830	864	1.508	810	685	72,5	10	51	1.520	832	853	835	10	51	54	USH0U14
LB-S1552-3Y-2T	1.570	830	864	1.508	810	685	72,5	9	51	1.520	832	853	835	9	51	54	USH0U14
LBT-S1552-3Y-2T	1.570	830	864	1.508	810	685	72,5	10	51	1.520	832	853	835	10	51	54	USH0U14
LB-S1556-3Y-2T	1.570	830	864	1.508	810	685	72,5	9	51	1.520	832	853	835	9	51	54	USH0U14
LBT-S1556-3Y-2T	1.570	830	864	1.508	810	685	72,5	10	51	1.520	832	853	835	10	51	54	USH0U14
LB-S2056-3Y-2T	1.570	830	864	1.508	810	685	72,5	9	51	1.520	832	853	835	9	51	54	USH0U14
LBT-S2056-3Y-4T	1.420	950	1.315	1.358	1.260	805	72,5	11	52	-	-	-	-	11	52	-	n.d.
LB-V2059-3Y-2T	1.570	915	885	1.508	810	685	72,5	13	53	1.520	917	938	835	13	53	59	USH0U22
LBT-V2059-3Y-4T	1.420	950	1.315	1.358	1.260	805	72,5	14	54	-	-	-	-	14	54	-	n.d.
LB-V1571-3Y-2T	1.420	915	690	1.358	635	685	72,5	12	53	1.370	917	838	880	12	53	48	USH0U23
LBT-V1571-3Y-2T	1.570	915	885	1.508	810	685	72,5	13	53	1.520	917	938	835	13	53	59	USH0U22
LB-V2571-3Y-2T	1.570	915	885	1.508	810	685	72,5	13	53	1.520	917	938	835	13	53	59	USH0U22
LBT-V2571-3Y-4T	1.420	950	1.315	1.358	1.260	805	72,5	14	54	-	-	-	-	14	54	-	n.d.
LB-V2084-3Y-2T	1.570	915	885	1.508	810	685	72,5	13	53	1.520	917	938	835	13	53	59	USH0U22
LBT-V2084-3Y-4T	1.420	950	1.315	1.358	1.260	805	72,5	14	54	-	-	-	-	14	54	-	n.d.
LB-V3084-3Y-4T	1.420	950	1.315	1.358	1.260	805	72,5	14	54	-	-	-	-	14	54	-	n.d.
LB-Z25106Y-3Y-4T	1.420	950	1.315	1.358	1.260	805	72,5	15	55	-	-	-	-	15	55	-	n.d.
LBT-Z25106-3Y-4T	1.420	950	1.315	1.358	1.260	805	72,5	15	55	-	-	-	-	15	55	-	n.d.
LB-Z30126Y-3Y-4T	1.420	950	1.315	1.358	1.260	805	72,5	15	55	-	-	-	-	15	55	-	n.d.
LBT-Z30126-3Y-4T	1.420	950	1.315	1.358	1.260	805	72,5	15	55	-	-	-	-	15	55	-	n.d.

① Condensing Unit without Protecting Housing

② Condensing Unit with Protecting Housing (supplied loose) see page 44